

# Capabilities



## Calcium fluoride prisms

The most frequently requested specifications for calcium fluoride prisms are as follows:

<b>Length of hypotenuse</b>	up-to $50 \pm 0.1$ mm
<b>Length of sides</b>	up-to $50 \pm 0.1$ mm
<b>Thickness</b>	$30 \pm 0.05$ mm
<b>Angle tolerance</b>	better than 1 arc minute
<b>Edge finish</b>	ground, blacked
<b>Clear aperture</b>	90% of entrance dimensions
<b>Chamfer</b>	$0.3 \times 0.3 @ 45^\circ$
<b>Form error</b>	better than $\lambda/4$ (633nm) over aperture
<b>Surface quality</b>	40-20 scratch/ dig

## Coatings

BBAR coating @2-10 $\mu$ m

Our capabilities are always expanding so if your requirement is not mentioned above please enquire as we have many years of experience in this field.

Contact our multilingual technical sales team and discover how Knight Optical's high quality calcium fluoride prism capabilities and service can improve your instrumentation and supply chain experience.

**KO** | BRINGING QUALITY INTO FOCUS

[www.knightoptical.com](http://www.knightoptical.com) | [info@knightoptical.com](mailto:info@knightoptical.com) | [usasales@knightoptical.com](mailto:usasales@knightoptical.com)



Knight Optical (UK) Limited © and Knight Optical USA LLC. Whilst every effort has been made to verify the information and data, Knight Optical can take no responsibility for its accuracy. All content on this page is protected under the Copyright, Designs and Patents Act 1988 and the Copyright © is owned by Knight Optical (UK) Limited 2011-2015. All rights are reserved. Reproduction of any content, by any means, without the express permission of the owner is prohibited by law. The KNIGHT OPTICAL name and/or mark and KO KNIGHT OPTICAL LOGO are the trademarks of Knight Optical (UK) Limited. Knight Optical (UK) Ltd is an ISO registered company.